MODEL

●PK-C3012

SPECIFICATION

- Capacity:1.5L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Cord storage
- LED ON/OFF LIGHT
- ANTI-SLIP FEET

CAPACITY
1.5L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.5L
N.W Per carton	11.2kg
G.W Per carton	12kg
Inner packing Measurement	20.5x16.5x21.8cm
Outer packing Measurement	67.5x21x46cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'3600pcs /1x40' 7800pcs 1x40HQ 5500pcs



MODEL

●PK-C3020

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Cord storage
- LED ON/OFF LIGHT
- ANTI-SLIP FEET

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	11.2kg
G.W Per carton	12kg
Inner packing Measurement	20.5x16.5x21.8cm
Outer packing Measurement	67.5x21x46cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'3600pcs /1x40' 4368pcs 1x40HQ 5552pcs





MODEL

●PK-C3016

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Cord storage
- LED ON/OFF LIGHT

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	8kg
G.W Per carton	9kg
Inner packing Measurement	23.5x20.5x23.5cm
Outer packing Measurement	63x25x49cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'2184pcs /1x40' 4368pcs 1x40HQ 5304pcs



MODEL

●PK-C3027

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Cord storage
- LED ON/OFF LIGHT
- ANTI-SLIP FEET

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	8kg
G.W Per carton	9kg
Inner packing Measurement	20.5x16.5x21.8cm
Outer packing Measurement	67.5x21x46cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'3600pcs /1x40' 7800pcs 1x40HQ 8264pcs

MODEL

●PK-C3028

SPECIFICATION

- Capacity:1.7L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Cord storage
- LED ON/OFF LIGHT
- ANTI-SLIP FEET

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	10.2kg
G.W Per carton	13.8kg
Inner packing Measurement	20.5x16.5x21.8cm
Outer packing Measurement	57.5x24.5x55.5cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'2400pcs /1x40' 4800pcs
	1x40HQ 5352pcs

MODEL

●PK-S1401

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Safety locking lid and cord storage
- LED ON/OFF LIGHT

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	18.5x15x18cm
Outer packing Measurement	46.5x38.5x38cm
Qty per carton	12pcs/ctn
Container loading quantity	1x20'4000pcs /1x40' 8000pcs
	1x40HQ 9000pcs

MODEL

●PK-C3029

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- LED ON/OFF LIGHT
- ANTI-SLIP FEET

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	8kg
G.W Per carton	9kg
Inner packing Measurement	20.5x16.5x21.8cm
Outer packing Measurement	67.5x21x46cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'3600pcs /1x40' 7800pcs
	1x40HQ 8264pcs

MODEL

●PK-S1401E

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Safety locking lid and cord storage
- LED ON/OFF LIGHT

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1300-1500W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	18.5x15x18cm
Outer packing Measurement	46.5x38.5x38cm
Qty per carton	12pcs/ctn
Container loading quantity	1x20'4000pcs /1x40' 8000pcs
	1x40HQ 9000pcs

MODEL

●PK-S1406

SPECIFICATION

- Capacity:1.7L
- 360 degree cordless base
- concealed S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- Cord storage

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	8kg
G.W Per carton	9kg
Inner packing Measurement	20.5x16.5x21.8cm
Outer packing Measurement	67.5x21x46cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3600pcs /1x40' 7800pcs
	1x40HQ 8264pcs

MODEL

●PK-1001

SPECIFICATION

- Capacity:1.0L
- S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- ON/OFF LIGHT

CAPACITY
1.0L

●GENERAL FEATURES	
Power	750-900W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	2.4kg
G.W Per carton	3.68kg
Inner packing Measurement	16x13x19.5cm
Outer packing Measurement	40.5x17.5x41cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'5960pcs /1x40' 10000pcs
	1x40HQ 13960pcs

MODEL

●PK-S1408

SPECIFICATION

- Capacity:1.0L
- 360 degree cordless base
- concealed S/S heating element
- Large spout with removable and washable scale filter
- Automatically cut off while boiling
- Boil dry and overheat protection
- Safety locking lid and cord storage
- LED ON/OFF LIGHT

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1350-1600W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	5.2kg
G.W Per carton	6kg
Inner packing Measurement	19.5x14x19cm
Outer packing Measurement	43.5x20.5x40cm
Qty per carton	6pcs/ctn
Container loading quantity	1x20'4710pcs /1x40' 9800pcs
	1x40HQ 11500pcs

MODEL

●PK-1008

SPECIFICATION

- Capacity:1.7L
- cordless base
- S/S heating element
- Automatically cut off while boiling
- Boil dry and overheat protection
- ON/OFF LIGHT

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	6kg
G.W Per carton	7kg
Inner packing Measurement	20x14.5x24cm
Outer packing Measurement	59.5x21.5x50cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3664pcs /1x40' 7800pcs
	1x40HQ 9000pcs

MODEL

MODEL

●PK-1008C

SPECIFICATION

- ●Capacity:1.7L
- ●cordless base
- ●S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●ON/OFF LIGHT

CAPACITY **1.7L**



●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	6kg
G.W Per carton	6.5kg
Inner packing Measurement	20x14.5x24cm
Outer packing Measurement	59.5x21.5x50cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3664pcs /1x40' 7800pcs
	1x40HQ 9000pcs

●PK-1009



MODEL

●PK-1009C

SPECIFICATION

- ●Capacity:1.7L
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection

CAPACITY **1.7L**

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	6.4kg
G.W Per carton	7kg
Inner packing Measurement	19.5x14.5x22cm
Outer packing Measurement	59.5x21x46cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'4000pcs /1x40' 8000pcs
	1x40HQ 9900pcs

MODEL

●PK-3008

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY **1.7L**



●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	7kg
G.W Per carton	8kg
Inner packing Measurement	20x16.5x22.5cm
Outer packing Measurement	67.5x21.5x47cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3200pcs /1x40' 6800pcs
	1x40HQ 8304pcs



MODEL

●PK-3010

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY **1.7L**

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	7kg
G.W Per carton	8kg
Inner packing Measurement	19.5x17x23.5cm
Outer packing Measurement	69.5x20.5x49cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2904pcs /1x40' 6640pcs
	1x40HQ 7616pcs

●PK-1010

SPECIFICATION

- ●Capacity:1.7L
- ●cordless base
- ●S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●ON/OFF LIGHT

CAPACITY **1.7L**



●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	6kg
G.W Per carton	7kg
Inner packing Measurement	20x14.5x24cm
Outer packing Measurement	59.5x21.5x50cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3664pcs /1x40' 7800pcs
	1x40HQ 9000pcs



MODEL

●PK-1010C

SPECIFICATION

- ●Capacity:1.7L
- ●cordless base
- ●S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●ON/OFF LIGHT

CAPACITY **1.7L**

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	6kg
G.W Per carton	7kg
Inner packing Measurement	20x14.5x24cm
Outer packing Measurement	59.5x21.5x50cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3664pcs /1x40' 7800pcs
	1x40HQ 9000pcs

MODEL

●PK-3018

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY **1.7L**



●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	7kg
G.W Per carton	8kg
Inner packing Measurement	20x16.5x22.5cm
Outer packing Measurement	67.5x21.5x47cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'3200pcs /1x40' 6800pcs
	1x40HQ 8304pcs



MODEL

●PK-3068

SPECIFICATION

- ●Capacity:1.0L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY **1.0L**

●GENERAL FEATURES	
Power	1350-1600W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	18.5x15x18cm
Outer packing Measurement	46.5x38.5x38cm
Qty per carton	12pcs/ctn
Container loading quantity	1x20'4000pcs /1x40' 8000pcs
	1x40HQ 9000pcs

MODEL

●PK-1068

MODEL

●PK-G916

SPECIFICATION

- ●Capacity:1.0L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.0L

●GENERAL FEATURES	
Power	1350-1650W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x51cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2744pcs /1x40' 5400pcs
	1x40HQ 6400pcs



SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	9kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs





MODEL

●PK-G915

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1800-2100W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2904pcs /1x40' 5800pcs
	1x40HQ 6912pcs



MODEL

●PK-G916S

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs

MODEL

●PK-G918B

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	9kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs



MODEL

●PK-G917

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23.5cm
Outer packing Measurement	75x22.5x49cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2704pcs /1x40' 5616pcs
	1x40HQ 6560pcs





MODEL

●PK-G918

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	9kg
G.W Per carton	10.7kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs



MODEL

●PK-G919

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1800-2100W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs

MODEL

●PK-G928

SPECIFICATION

- ●Capacity:2.0L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
2.0L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	2.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x24cm
Outer packing Measurement	75x22.5x50cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2704pcs /1x40' 5504pcs
	1x40HQ 6480pcs



MODEL

●PK-G956

SPECIFICATION

- ●Capacity:2.0L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
2.0L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	2.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs





MODEL

●PK-G928B

SPECIFICATION

- ●Capacity:2.0L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
2.0L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	2.0L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x184x24.5cm
Outer packing Measurement	75x22.5x51cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2744pcs /1x40' 5400pcs
	1x40HQ 6400pcs



MODEL

●PK-G958

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	9kg
G.W Per carton	10.7kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs

MODEL

●PK-G958B

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	9kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs



MODEL

●PK-G998-S

SPECIFICATION

- ●Capacity:1.5L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.5L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.5L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs





MODEL

●PK-G997

SPECIFICATION

- ●Capacity:1.7L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.7L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.7L
N.W Per carton	9kg
G.W Per carton	10.7kg
Inner packing Measurement	21.5x18.4x23cm
Outer packing Measurement	75x22.5x48cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2800pcs /1x40' 5800pcs
	1x40HQ 6912pcs



MODEL

●PK-G998-O

SPECIFICATION

- ●Capacity:1.5L
- ●360 degree cordless base
- ●concealed S/S heating element
- ●Automatically cut off while boiling
- ●Boil dry and overheat protection
- ●Illumination light

CAPACITY
1.5L

●GENERAL FEATURES	
Power	1850-2200W
Voltage/Frequency	220-240V~/50Hz
Capacity	1.5L
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	21.5x184x24.5cm
Outer packing Measurement	75x22.5x51cm
Qty per carton	8pcs/ctn
Container loading quantity	1x20'2744pcs /1x40' 5400pcs
	1x40HQ 6400pcs

MODEL

●PE-138

MODEL

●PC-168

SPECIFICATION

- 3 Eggs
- Aluminum heat element
- Anti-Slip feet
- Automatic off

CAPACITY
3Eggs



●GENERAL FEATURES	
Power	210W
Voltage/Frequency	220-240V~/50Hz
Capacity	5Eggs
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	22x10x13.5cm
Outer packing Measurement	45x31x28.5cm
Qty per carton	12pcs/ctn
Container loading quantity	1x20'8448pcs /1x40' 17496pcs 1x40HQ 20520pcs

MODEL

●PE-158



SPECIFICATION

- Capacity:5Eggs
- Aluminum heat element
- Anti-Slip Feet
- Automatic off

CAPACITY
5Eggs

●GENERAL FEATURES	
Power	210W
Voltage/Frequency	220-240V~/50Hz
Capacity	5Eggs
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	16x13.5x15cm
Outer packing Measurement	41.5x33x31.5cm
Qty per carton	12pcs/ctn
Container loading quantity	1x20'7788pcs /1x40' 16218pcs 1x40HQ 18912pcs

SPECIFICATION

- Capacity:120g

CAPACITY
120g



●GENERAL FEATURES	
Power	200W
Voltage/Frequency	220-240V~/50Hz
Capacity	120g
N.W Per carton	10kg
G.W Per carton	11kg
Inner packing Measurement	8.7x8.7x17.2cm
Outer packing Measurement	27.1x27.1x35.9cm
Qty per carton	12pcs/ctn
Container loading quantity	1x20'12744pcs /1x40' 26400pcs 1x40HQ 30948pcs