

Garment Steamer Series	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	0
-------------------------------	--	---



Steam Generator Series 0.	Steam Generator Series		0	17.1
---------------------------	------------------------	--	---	------



Steam Cleaner Series	05
----------------------	----



Cordless Steam	Iron Series	 08



















Dry Iron Series ------ 37

Garment Steamer Series

Handheld Garment Steamer PS-0022



FEATURES:

- Instantly refresh your clothes, remove wrinkles, clean and sterilize clothes in no time
- Versatile- suitable for a variety of fabrics including cotton, wool, polyester, plush, silk, fiber, nylon
- Useful accessories Fabric brush to brush away wrinkles, steam bonnet to prevent any type of dripping water from staining your garments
- Removable water tank is easy to clean and refill, compact design for travel or business trip
- Power: 1200-1600W for USA and 1500W for Europe
- Voltage: 220-240V/100-127V
- Frequency: 50/60Hz
- Water Tank Capacity: 250ml
- Unit size: 163x134x296mm
- Soleplate Size: 115x65mm
- Continuous Steam Rate: 24±4g/min
- Steam ready time: 30 s
- With pump
- Exchangeable anti-calc filter
- With steam lock switch
- Auto Shut-Off in 8 minutes when not used
- Water tank lasts for up to about 10 minutes of continuous steam
- Packing details as follows:

6pcs per carton

Giftbox size: 21.3x16.5x31.5CM

Carton Size: 51.5x45x34cm

2160pcs/20'FCL; 4350pcs/40'FCL; 4950pcs/40HQ

• CE/GS/CB/RoHS approval







FEATURES:

- Instantly refresh your clothes, remove wrinkles, clean and sterilize clothes in no time
- Versatile-suitable for a variety of fabrics including cotton, wool, polyester, plush, silk, fiber, nylon
- Useful accessories Fabric brush to brush away wrinkles, steam bonnet to prevent any type of dripping water from staining your garments
- Removable water tank is easy to clean and refill, compact design for travel or business trip
- Power: 1200-1600W for USA and 1500W for Europe
- Voltage: 220-240V/100-127V
- Frequency: 50/60Hz
- Water Tank Capacity: 250ml
- Unit size: 115x148x303mm
- Continuous Steam Rate: 22 ± 5g/min
- Steam ready time: 30 s
- With pump
- Exchangeable anti-calc filter
- With steam lock switch
- Water tank lasts for up to about 10 minutes of continuous steam
- Adsorption fittings
- Packing details as follows:
- 6pcs per carton
- Giftbox size: 21.3x16.5x31.5CM
- Carton Size: 51.5x45x34cm
- 2160pcs/20'FCL; 4350pcs/40'FCL; 4950pcs/40HQ
- CE/GS/CB/RoHS approval





Steam Generator Series

Steam Generator Iron SG-8858

- coating/nano ceramic coating/
 titanium coating
 lock and carry features

 Soleplate size: 233x120mm
 Unit size: 430x256x280mm
 Continuous steam rate: 90±10g/min titanium coating
 • lock and carry features
- With water empty alarm
- Detachable water tank
 Adjustable temperature
- ECO design mode • De-Cale design, easy to remove
- the calc accumulated
- Power for steam iron: 850W
 Power for boiler: 1370W
- Voltage:220-240V/100-127V
- Frequency: 50/60Hz

- Soleplate: non-stick/ceramic Water tank capacity: 1700ml

 - Boiler pressure: 6.5-7.0 Bar

 - Steam Ready time: 2-3 minutes
 Packing details as follows
 1pc/Carton Giftbox Size: 47.4x29.4x32cm
 - Carton Meas.: 50x30.5x34cm 20'=540pcs; 40'=1085pcs; 40'HQ=1245pcs
 - CE/GS/CB/RoHS approval









Steam Station Iron SG-8868

FEATURES:

- Adjustable temperature
- Soleplate: non-stick/ceramic coating/nano ceramic coating/ stainless steel
- Water shortage alert
- ECO Adjustable steam level
 Exchangeable anti-calc filter
 Power: 1200-2400W
- Voltage:220-240V/100-127V
- Voltage: 220-240V/100-127V
 Frequency: 50/60Hz
 Steam Rate: 100±15g/min
 Watertank capacity: 2000ml
 Soleplate size: 231X120mm
- Unit size: 370x196x250mm Steam ready time: 1 minute
- Carton Meas.: 45.5x29x3lcm 20'=663pcs; 40'=1363pcs; 40'HQ=1858pcs • CE/GS/CB/RoHS approval

Packing details as follows 1pc/Carton Giftbox Size: 42.5x27.5x28cm













Steam Generator Iron SG-2801

FEATURES:

- Composite Ceramic Coating Soleplate
- lock and carry features
- With water empty alert and tone
- Detachable water tank
- Adjustable temperature
- Resistance temperature control mode
- ECO design mode
- De-Cale alert design, easy to remove the calc accumulated
- Wattage: 2200W-2800W
- Voltage:220-240V/100-127V
- Frequency: 50/60Hz
- Water tank capacity: 1900ml
- Soleplate size: 227x121mm
- Unit size: 430x245x280mm
- Unit weight: 4400g
- ullet Two temperature level: MAX 160±16 $^{\circ}{\mathbb C}$;
- Lower Level: 120±15℃
- Burst of steam rate: 500±30g/min
- Continuous steam rate: 120g±15g/min
- Boiler pressure: 7±0. 5 bar
- Steam Ready time: 3 minutes
- Power On tone
- Auto Shut-Off in 10 minutes when not used
- Packing details as follows
- 1pc/Carton
- Giftbox Size: 47.4x29.4x32cm Carton Meas.: 50x30.5x34cm
- 20'=540pcs; 40'=1085pcs; 40'HQ=1245pcs
- CE/GS/CB/RoHS approval





Portable Steam Cleaner SC-1001

FEATURES:

- Continuous Steam
- Heating Time: 12s
- Water Tank Capacity: 250ml
- Power: 1500W
- Voltage: AC120V/AC220-240V
- Steam Pressure: 3.5 Bar
- Working Time: 15 min.
- Unit Net Weight: 1.4 Kgs.
- Accessories: Glass brush, elbow nozzle, big pick head, small round brush, small round nozzle, extension fitting sleeve pipe
- Steam temperature: 100 ℃
 Steam temperature 91 degrees away from nozzle 5mm
- Steam Rate: 15-20g/min.
- Multiple connections and scenarios
- Multiple security production
- Longer hose for more flexibility
- Long steam injection distance of 0.8 m
- Unit size: 317*108*234mm
- Packing Details to be fixed
- CE/GS/ETL to be applied





Cordless Steam Iron 3001RW Series

FUNCTIONS

- Dry/spray/steam/burst of steam/ self-cleaning
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/Titanium coating/stainless steel
- Innovative cord retractable designs, never worry about the cord hitting your hand
- Optional features: anti-calc/anti-
- · Optional smart heating alert
- technology Overheat safety protection circuit
- · Room space-saving design
- · Ionic nano ceramic coating optional

- SPECIFICATIONS
 Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
 Water tank capacity: 270ml
- Soleplate size: 229x121mm
- Unit size: 178x178x337mm
- . Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows

6pcs/Carton

Giftbox Size: 19.5x19.5x35.2cm Carton Meas.: 60.5x40.5x37.5cm 20'=1704pcs; 40'=3540pcs;

40'HQ=3966pcs

Model No.: UHC-3001RW only for American market with ETL/CETL approval

Model No.: HC-3001RW for all the other counries except USA with CE/GS/CB/EMC/LVD/RoHS







Low temperature smart alert by red light







Ready for ironing by green light



Cordless Steam Iron Series

Cordless Steam Iron 3002RW Series

- FUNCTIONS

 Dry/spray/steam/burst of steam/
 self-cleaning
 Soleplate: Non-Stick/Ceramic
- coating/NanoCeramic/Titanium coating/stainless steel
- · Innovative cord retractable designs, never worry about the cord hitting your hand
- Optional features: anti-calc/anti-
- Optional smart heating alert technology
- Overheat safety protection circuit 20'=1704pcs; 40'=3540pcs; Room space-saving design
- · Ionic nano ceramic coating optional

- SPECIFICATIONS
 Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60HzWater tank capacity: 350ml
- Soleplate size: 229x121mm
- Unit size: 178x178x339mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
 Packing details as follows

6pcs/Carton

Giftbox Size: 19.5x19.5x35.2cm Carton Meas.: 60.5x40.5x37.5cm

40'HQ=3966pcs

Model No.: UHC-3002RW only for American market with ETL/CETL approval

Model No.: HC-3002RW for all the other counries except USA with CE/GS/CB/EMC/LVD/RoHS



FEATURES:

- Dry/spray/steam/burst of steam/Cordless
- Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/Titanium coating/stainless steel
- Innovative cord retractable designs, never worry about the cord hitting your hand
- Optional features: anti-calc/anti drip Optional smart heating alert technology
- Room space-saving design
- Power: 1200-1800W
- Voltage:220-240V/100-127V
- Frequency: 50/60Hz
- Water tank capacity: 180ml
- Soleplate size: 198x105mm
- Unit size: 188x178x324mm • Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min
- Packing details as follows

6pcs/Carton

Giftbox Size: 19.5x19.5x35.2cm Carton Meas.: 60.5x40.5x37.5cm

20'=1704pcs; 40'=3540pcs; 40'HQ=3966pcs

Model No.: HC-3003RW only for American market with ETL/CETL approval

Model No.: HC-3003RW for all the other counries except USA with CE/GS/CB/EMC/LVD/RoHS



Steam Iron with pump system

Steam Iron with pump system SG-8001

FUNCTIONS

- Dry/spray/steam/burst of steam/ self-cleaning/LCD/Auto Shut-Off/ Pump system
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/Titanium coating/stainless steel
- High accurate electronic temperature control
- Continuous steam ironing/ continuous vertical steam ironing
- · Electronic programmable steam · Optional features: anti-calc/anti-
- · Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS

- Power: 1200-3250W
 Voltage:220-240V/100-127V
- Frequency: 50/60Hz
- · Water tank capacity: 470ml Soleplate size: 237x129mm
- Unit size: 310x158x155mm
- Burst of steam rate: 0.6-1.0g/
- · Continuous steam rate: 25-35g/min
- Packing details as follows
- 6pcs/Carton Giftbox Size: 33.4x17.4x16.9cm Carton Meas.: 54.5x34.4x36cm
- 20'=2298pcs; 40'=4746pcs; 40'HQ=5538pcs









- coating/NanoCeramic/Titanium coating/stainless steel · Optional features: anti-calc/anti-
- drip/auto shut-off/sensor Overheat safety protection
- Overheat safety protection
- circuit

CE/GS/CB/RoHSapproval

- Frequency: 50/60Hz · Water tank capacity: 470ml
- Soleplate size:230x120mm
- Unit size: 313x125x165mm
- . Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 20-30g/
- Packing details as follows

6pcs/Carton Giftbox Size: 32.2x13.1x16.6cm Carton Meas.: 54.5x33x35.2cm 20'=3560pcs; 40'=7360pcs; 40'HQ=8080pcs




LED Steam Iron SG-5008E

- Dry/spray/steam/burst of steam/self- cleaning/LED/Auto Shut-Off
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
 Optional features: anti-calc/
- anti-drip
- Overheat safety protection circuit CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS

- Power: 1200-3250W
 Voltage:220-240V/100-127V
- Frequency: 50/60Hz
- Water tank capacity: 390ml
- Soleplate size: 237x129mm
 Unit size: 310x128x155mm
- · Burst of steam rate: 0.6-1.0g/time
- Continuous steam rate: 25-35g/min Packing details as follows
- 10pcs/Carton Giftbox Size: 32.2x15x16.9cm
- Carton Meas.: 77.5x33.3x35.9cm 20'=3050pcs; 40'=6230pcs;





LED Steam Iron SG-5058E

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/LED/Auto
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- · Optional features: anti-calc/
- Overheat safety protection circuit CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
 Water tank capacity: 280ml
- Soleplate size: 229x121mm
- Unit size: 295x120x150mm
- Burst of steam rate: 0.3-0.5g/time
 Continuous steam rate: 15-25g/min
- · Packing details as follows

10pcs/Carton Giftbox Size: 30.5x12.4x15.7cm Carton Meas.: 65x31.5x33.5cm 20'=4150pcs; 40'=8310pcs; 40'HQ=9520pcs

LCD Steam Iron SG-5058D

- Dry/spray/steam/burst of steam/self-cleaning/LCD/Auto Shut-Off
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature control
 Optional features: anti-calc/
- anti-drip
- Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2200W
 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 280ml
 Soleplate size: 229x121mm
- Unit size: 295x120x150mm
- Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
 Packing details as follows
- 10pcs/Carton Giftbox Size: 30.5x12.4x15.7cm Carton Meas.: 65x31.5x33.5cm 20'=4150pcs; 40'=8310pcs;



LCD Steam Iron SG-5006D

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/LCD/Auto Shut-Off
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- · Optional features: anti-calc/ Overheat safety protection
- circuit CE/GS/CB/RoHS approval

- SPECIFICATIONS

 Power: 1200-2200W

 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
 Water tank capacity: 300ml
- Soleplate size: 229x121mm
- Unit size: 305x121x150mm
- Burst of steam rate: 0.4-0.6g/time
 Continuous steam rate: 15-25g/min · Packing details as follows
- 10pcs/Carton Giftbox Size: 32.8x13.3x176.2cm Carton Meas.: 69x33.9x34.4cm 20'=2880pcs; 40'=6100pcs; 40'HQ=7130pcs

Travel Steam Iron Series

Travel Steam Iron HT-2001

FUNCTIONS

- Dry ironing without wet clothes
- · Small size with light weight, easy to carry for business or personal travel
- Easy daily work accompanying
 Small and light, precise quick
- ironing, your good travel

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1000W
- Voltage:220-240V/100-127V/50/60Hz
 Frequency: 50/60Hz
- · Water tank capacity: 90ml Unit size:174x92x154mm
- Unit weight:0.6 Kgs
- Continuous steam rate: 5-16g/min
- Steam level 1: 7g/min.; suitable for cotton, silk fabrics
- · Steam level 2: 14g/min, suitable for woolen or plush fabrics
- · Base can be locked and connected with

6pcs/Carton

Giftbox Size: 22x9.5x17.5cm Carton Meas.: 30.5x23x37.1cm 20'=5832pcs; 40'=12078pcs; 40'HQ=13536pcs









High-End Steam Iron HL-8010

FEATURES:

- Dry/Spray/Steam/Burst of seam/self-cleaning
- Optional features: Anti-calc/ Anti-Drip/Auto Shut-Off
- Two-color lights remind temperature change of soleplate
- Power: 2200W-3000W
- Voltage: AC220-240V/100-127V
- Frequency: 50/60Hz
- Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/ Titanium/Coating/Stainless Steel
- Water Tank capacity: 300ml
- High accurate temperature
- Unit size: 310x146x152mm
- Soleplate Size:237x129mm
- Overheat safety protection circuit
- Continuous Steam Rate: 20-30g/min.
- Burst of Steam Rate: 0.6-0.8g/time
- CE/GS/CB/RoHS/approval
- Packing details as follows:

6pcs per carton

Giftbox size: 32.5x15x16.9cm

Carton Size: 46.9x33.5x35.9cm

2880pcs/20'FCl; 6048pcs/40'FCL;6750pcs/40HQ

• CE/GS/CB/RoHS approval







High-End Steam Iron HL-8012

FEATURES:

- Dry/spray/steam/burst of steam/self-cleaning
- Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/Titanium coating/ stainless steel
- High accurate temperature control
- 63 steam holes
- Optional features: anti-calc/anti-drip/auto shut-off
- Overheat safety protection circuit
- Power: 2200W-3000W
- Voltage:220-240V/100-127V
- Frequency: 50/60Hz
- Water tank capacity: 480ml
- Soleplate size: 251x131mm
- Unit size: 317*150*160mm
- Burst of steam rate: 0.7-0.9g/time
- Continuous steam rate: 45-55g/min
- High-Level Aluminum Soleplate with Ceramic Coating
- Aluminum soleplate weight: 510g
- The total weight of Aluminum soleplate with steam chamber + heating element + wrapped cover: 720g
- Exchangeable anti-calc filter
- Packing details as follows

6pcs/Carton

Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm

G.W./N.W.: 11.4/10.14Kgs.

20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs

• CE/GS/CB/RoHS approval







Powerful High-End Steam Iron Series

Powerful High-End Steam Iron HL-8001

- Dry/spray/steam/burst of steam/self-cleaning/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/Titanium coating/stainless steel
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-3250W
 Voltage:220-240V/100-
- 127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 350ml
 Soleplate size: 237x129mm
- Unit size: 310x128x150mm

- Burst of steam rate: 0.6-0.8g/time
 Continuous steam rate: 20-30g/min
 Packing details as follows 6pcs/Carton

Giftbox Size: 32.5x15x16.9cm Carton Meas.: 46.9x33.5x35.9cm G.W./N.W.: 10.5/9.85Kgs. 20'=2880pcs; 40'=6048pcs; 40'HQ=6750pcs





Powerful High-End Steam Iron HL-8002

FUNCTIONS

- Dry/Spray/Steam/Burst of
- Steam/Self-Cleaning
 Soleplate: Non-Stick/Ceramic Coating/Nano Ceramic/Titanium • Water Tank Capacity: 350ml Coating/Stainless Steel
- High accurate temperature control
- Overheat safety protection
- circuit Optional features: Anti-Calc/
- Anti-Drip/Auto Shut-Off
 CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-3000W
- Voltage: 220-240V/100-127V Frequency: 50/60Hz
- Open Handle Design
- Unit size: 310x128x150mm
- Soleplate Size:237x129mm
- · Continuous Steam Rate: 20-30g/min.
- Burst of Steam Rate: 0.6-0.8g/time
- · Packing details as follows: 6pcs per carton Giftbox size: 32.5x15x16.9cm Carton Size: 46.9x33.5x35.9cm 2880pcs/20'FCL; 6048pcs/40'FCL; 6750pcs/40HQ





Powerful High-End Steam Iron Series

Powerful High-End Steam Iron SG-5007

FUNCTIONS

- · Dry/spray/steam/burst of steam/self-cleaning/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/Titanium • Water tank capacity: 320ml coating/stainless steel • Soleplate size: 237x129mm
- · High accurate temperature · Optional features: anti-calc/
- anti-drip/auto shut-off
- Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Unit size: 304x137x154mm Burst of steam rate: 0.6-1.0g/time
- Continuous steam rate: 25-35g/min
- · Packing details as follows 6pcs/Carton Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm

G.W./N.W.: 11.4/10.14Kgs. 20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs

Giftbox Size: 32.2x15x16.9cm

10pcs/Carton







FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off
- · Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS

- Power: 1200-3250W
 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 390ml Soleplate size: 237x129mm
- Unit size: 310x128x150mm
- . Burst of steam rate: 0.6-1.0g/time
- · Continuous steam rate: 25-35g/min
- · Packing details as follows 6pcs/Carton
- Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm G.W./N.W.: 11.4/10.14Kgs. 20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs









Powerful High-End Steam Iron SG-8002

FUNCTIONS

- · Dry/spray/steam/burst of
- steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz
 Frequency: 50/60Hz
- · Water tank capacity: 400ml
- Soleplate size: 237x129mm
- Unit size: 305x136x157mm
- . Burst of steam rate: 0.6-1.0g/time
- Continuous steam rate: 20-30g/min
- · Packing details as follows 6pcs/Carton

Giftbox Size: 33.3x14.6x17.5cm Carton Meas,: 46x34.3x37.1cm G.W./N.W.: 10.4/9.6Kgs. 20'=2880pcs; 40'=6060pcs; 40'HQ=7020pcs











Powerful High-End Steam Iron SG-8003



FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-3250W
 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 400ml Soleplate size: 237x129mm
- Unit size: 311x136x154mm
- . Burst of steam rate: 0.6-1.0g/time
- Continuous steam rate: 20-30g/min
- Packing details as follows 6pcs/Carton

Giftbox Size: 33.3x14.6x17.5cm Carton Meas.: 46x34.3x37.1cm G.W./N.W.: 10.4/9.6Kgs. 20'=2880pcs: 40'=6060pcs: 40'HQ=7020pcs









Powerful High-End Steam Iron SG-8005

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/ETL/CETL/RoHS

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 470ml
- Soleplate size: 248x125mm
- Unit size: 303x165x123mm
- · Burst of steam rate: 0.6-1.0g/time Continuous steam rate: 20-30g/min
- Packing details as follows

6pcs/Carton Giftbox Size: 33x13x18.5cm Carton Meas.: 41x34x39cm G.W./N.W.: 10.4/9.6Kgs. 20'=3000pcs; 40'=6000pcs;

40'HQ=7140pcs



Powerful High-End Steam Iron SG-8006

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning/ Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/ Titanium coating/stainless steel
- · High accurate temperature
- · Optional features: anti-calc/
- anti-drip/auto shut-off
- · Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-3250W Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 400ml
 Soleplate size: 248x125mm
- Unit size: 302x160x123mm Burst of steam rate: 0.6-1.0g/time
- Continuous steam rate: 20-30g/min
- · Packing details as follows 6pcs/Carton Giftbox Size: 33x13x18.5cm

Carton Meas.: 41x34x39cm G.W./N.W.: 10.4/9.6Kgs. 20'=3000pcs; 40'=6000pcs; 40'HQ=7140pcs

Powerful High-End Steam Iron SG-8007

FUNCTIONS

circuit

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control · Optional features: anti-calc/
- anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 380ml Soleplate size: 237x129mm
- Unit size: 310x128x150mm
- · Burst of steam rate: 0.6-0.8g/time Continuous steam rate: 20-30g/min
- Packing details as follows 6pcs/Carton Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm

20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs







Powerful High-End Steam Iron SG-8008

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Cerami coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
- Water tank capacity: 390ml
- Soleplate size: 237x129mm
- Unit size: 310x138x150mm
- · Burst of steam rate: 0.6-0.8g/time
- Continuous steam rate: 20-30g/min
- Packing details as follows 6ocs/Carton Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm G.W./N.W.: 11.4/10.14Kgs. 20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs 10pcs/Carton
- Giftbox Size: 32.2x15x16.9cm Carton Meas.: 77.5x33.3x35.9cm G.W./N.W.: 16/15Kgs. 20'=3050pcs; 40'=6230pcs; 40'HQ=7130pcs





Powerful High-End Steam Iron SG-8009

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- High accurate temperature
- Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoH5 approval

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 420ml
- Soleplate size: 237x129mm
 Unit size: 310x138x150mm
- · Burst of steam rate: 0.6-0.8g/time
- Continuous steam rate: 20-30g/min
- Packing details as follows
- 6pcs/Carton Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm G.W./N.W.: 11.4/10.14Kgs. 20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs



Powerful High-End Steam Iron SG-8808

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-3250W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 390ml Soleplate size: 237x129mm
- Unit size: 310x138x150mm
- · Burst of steam rate: 0.6-0.8g/time
- Continuous steam rate: 20-30g/min
- · Packing details as follows

6pcs/Carton Giftbox Size: 32.2x15x16.9cm Carton Meas.: 46.9x33.3x35.9cm G.W./N.W.: 11.4/10.14Kgs. 20'=2988pcs; 40'=6138pcs; 40'HQ=7224pcs 10pcs/Carton Giftbox Size: 32.2x15x16.9cm

Carton Meas.: 77,5x33.3x35.9cm G.W./N.W.: 16/15Kgs. 20'=3050pcs; 40'=6230pcs; 40'HQ=7130pcs

Economic Steam Iron SG-5516

FUNCTIONS

- · Dry/spray/steam/burst of
- steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off
- · Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 280ml
- Soleplate size: 231x120mm
- Unit size: 290x123x140mm
 Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows 8pcs/Carton

Giftbox Size: 31x12.5x16.5cm Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950ocs: 40'=8100ocs: 40'HQ=9200pcs



Economic Steam Iron SG-5518

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature
- Optional features: anti-calc/
- Overheat safety protection

CE/GS/CB/RoHS approval

- Frequency: 50/60Hz
 Water tank capacity: 280ml
- control
- anti-drip/auto shut-off

SPECIFICATIONS

- Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Soleplate size: 231x120mm
- Unit size:320x133x145mm
- . Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min

 Packing details as follows 8pcs/Carton Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs

Economic Steam Iron HM-7001

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/RoHS approval

SPECIFICATIONS Power: 1200-2600W

- Voltage:220-240V/100-127V/50/60Hz
 Frequency: 50/60Hz
- · Water tank capacity: 260ml Soleplate size: 231x120mm
- Unit size: 286x123x144mm
- · Burst of steam rate: 0.4-0.6g/time
- · Continuous steam rate: 15-25g/min · Packing details as follows 10pcs/Carton Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 14/13Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs



Economic Steam Iron SG-5501

FUNCTIONS

circuit

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/RoHS approval

SPECIFICATIONS

Power: 1200-2600W

- Frequency: 50/60Hz Water tank capacity: 300ml
- Soleplate size: 231x120mm Unit size: 292x119x143mm

Voltage:220-240V/100-127V/50/60Hz

- Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min
 Packing details as follows
- 8pcs/Carton Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs



FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/
- Titanium coating/stainless · High accurate temperature
- control · Optional features: anti-calc/ anti-drip/auto shut-off
- · Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2600W
 Voltage:220-240V/100-127V/50/60Hz Frequency: 50/60Hz
- Water tank capacity: 260ml
- Soleplate size: 231x120mm
- Unit size: 290x120x145mm
- · Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min Packing details as follows
- 8pcs/Carton Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs





Economic Steam Iron SG-5505

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature
- anti-drip/auto shut-off Overheat safety protection

SPECIFICATIONS

- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz

- Packing details as follows
- 8pcs/Carton

CE/GS/CB/RoHS approval

- Optional features: anti-calc/
- circuit

- Power: 1200-2600W

- Water tank capacity: 270ml
- Soleplate size: 231x120mm
 Unit size: 292x125x143mm
- . Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min
- Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs

Economic Steam Iron SG-5506

FUNCTIONS

circuit

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz Water tank capacity: 270ml
- Soleplate size: 231x120mm
- Unit size: 295x120x145mm
- Burst of steam rate: 0.4-0.6g/time
 Continuous steam rate: 15-25g/min
- Packing details as follows 8pcs/Carton Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs



Economic Steam Iron SG-5507

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off · Overheat safety protection
- CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 230ml
- Soleplate size: 231x120mm
- Unit size: 294x122x142mm · Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows 8pcs/Carton

Giftbox Size: 31.3x12.5x16.5cm Carton Meas.: 65x32.5x35cm

G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs: 40'=8100pcs: 40'HQ=9200pcs



Economic Steam Iron SG-5508

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel

- Overheat safety protection circuit

CE/GS/CB/RoHS approval

- Frequency: 50/60Hz
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off

SPECIFICATIONS

- Power: 1200-2600W
 Voltage:220-240V/100-127V/50/60Hz
 - Water tank capacity: 240ml
 - Soleplate size: 231x120mm
 Unit size: 296x120x143mm
 - · Burst of steam rate: 0.4-0.6g/time
 - Continuous steam rate: 15-25g/min Packing details as follows 8pcs/Carton

Giftbox Size: 31.3x12.5x16.5cm Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs

Economic Steam Iron SG-5509

FUNCTIONS

circuit

- . Dry/spray/steam/burst of
- steam/self-cleaning/ Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz · Water tank capacity: 300ml
- Soleplate size: 231x120mm
- Unit size: 290x123x140mm Burst of steam rate: 0.4-0.6g/time
- · Continuous steam rate: 15-25g/min · Packing details as follows

8pcs/Carton Giftbox Size: 31.3x12.5x16.5cm Carton Meas.: 65x32.5x35cm G.W./N.W.: 11.4/10.14Kgs. 20'=3950pcs; 40'=8100pcs;





40'HQ=9200pcs







Economic Steam Iron Series

Economic Steam Iron SG-6006

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
 Soleplate: Non-Stick/Ceramic
 Power: 1200-2000W
 Voltage:220-240V/100
 Frequency: 50/60Hz coating/NanoCeramic/
- Titanium coating/stainless steel · High accurate temperature
- control • Optional features: anti-calc/
- anti-drip/auto shut-off

 Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Voltage:220-240V/100-127V/50/60Hz
- · Water tank capacity: 250ml
- Soleplate size: 205x111mm
 Unit size: 270x113x133mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- · Packing details as follows 10pcs/Carton

Giftbox Size: 30x12x15.3cm Carton Meas.: 62.5x31.5x32.7cm G.W./N.W.: 11.4/10.14Kgs. 20'=4400pcs; 40'=9020pcs; 40'HQ=10100pcs





Economic Steam Iron SG-6007

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection

CE/GS/CB/ETL/CETL/RoHS

- SPECIFICATIONS

 Power: 1200-2000W

 Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
- Water tank capacity: 250ml
 Soleplate size: 205x111mm
- Unit size: 270x111x136mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
 Packing details as follows

10pcs/Carton Giftbox Size: 30x12x15.3cm Carton Meas.: 62.5x31.5x32.7cm G.W./N.W.: 11.4/10.14Kgs. 20'=4400pcs; 40'=9020pcs; 40'HQ=10100pcs







Economic Steam Iron HA-1002

- Dry/spray/steam/burst of steam
- Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/Titanium coating/stainless steel

 Optional features: anti-calc/antidrip
- Power: 1200-2000W

- Voltage:220-240V/100-127V
 Frequency:50/60Hz
 Water tank capacity: 250ml
 Soleplate size: 205X111mm
- Unit size: 270X111X136mm
- Burst of steam rate: 0.3-0.5g/timeContinuous steam rate: 15-25g/min
- Packing details as follows 6pcs/Carton Giftbox Size: 30X12X15.3CM Carton Meas.: 62.5X31.5X32.7CM
- 20'=4400pcs; 40'=9020pcs; 40'HQ=10100pcs • CE/GS/CB/RoHS approval









Economic Steam Iron SG-6001

FUNCTIONS

- Dry/spray/steam/burst of
- steam/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz · Water tank capacity: 200ml
- Soleplate size: 198x105mm
 Unit size: 270x107x132mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows 10pcs/Carton
- Giftbox Size: 29.5x12x14.8cm Carton Meas.: 62.5x30.5x31.7cm G.W./N.W.: 9/8Kgs. 20'=4400pcs; 40'=9250pcs;

40'HQ=10600pcs



circuit

- Dry/spray/steam/burst of
- steam/
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc Overheat safety protection
- CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 200ml
- Soleplate size: 198x105mm
 Unit size: 270x107x132mm
- · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min Packing details as follows
- 10pcs/Carton Giftbox Size: 29.5x12x14.8cm
- Carton Meas.: 62.5x30.5x31.7cm G.W./N.W.: 9/8Kgs. 20'=4400pcs; 40'=9250pcs; 40'HQ=10600pcs





Economic Steam Iron SG-6003

FUNCTIONS

- Dry/spray/steam/burst of steam/
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature
- · Optional features: anti-calc Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 200ml
- Soleplate size: 198x105mm Unit size: 266x107x130mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows 10pcs/Carton

Giftbox Size: 29.5x12x14.8cm Carton Meas.: 62.5x30.5x31.7cm G.W./N.W .: 9/8Kgs. 20'=4400pcs; 40'=9250pcs; 40'HQ=10600pcs

Economic Steam Iron SG-6005

FUNCTIONS

- . Dry/spray/steam/burst of steam/
- Soleplate: Non-Stick/Ceramic Frequency: 50/60Hz coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
- Voltage:220-240V/100-127V/50/60Hz
- Water tank capacity: 200ml
- Soleplate size: 198x105mm
- Unit size: 268x105x148mm
- Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min Packing details as follows
- 10pcs/Carton Giftbox Size: 29.5x12x14.8cm Carton Meas.: 62.5x30.5x31.7cm G.W./N.W.: 9/8Kgs. 20'=4400pcs; 40'=9250pcs; 40'HQ=10600pcs



Economic Steam Iron SG-5788

- Dry/spray/steam/burst of steam/
 • Soleplate: Non-Stick/Ceramic
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1400W
- Voltage:220-240V/100-127V/50/60Hz Frequency: 50/60Hz
- Water tank capacity: 100ml

 - Soleplate size: 198x105mm
 Unit size: 245x105x120mm
 - · Burst of steam rate: 0.3-0.5g/time
 - Continuous steam rate: 10-20g/min
 - Packing details as follows
 - 10pcs/Carton Giftbox Size: 27.2x11.2x13.8cm

Carton Meas.: 59.5x28.5x30cm G.W./N.W.: 12/11Kgs. 20'=5280pcs; 40'=11190pcs; 40'HQ=12790pcs



Economic Steam Iron SG-5068

FUNCTIONS

- Dry/spray/steam/burst of steam/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature
- · Optional features: anti-calc/ auto shut-off Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

circuit

SPECIFICATIONS

- Power: 1200-1800W
 Voltage: 220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
 - Water tank capacity: 180ml
 - Soleplate size: 198x105mm
 Unit size: 270x105x130mm
 - . Burst of steam rate: 0.3-0.5g/time
 - Continuous steam rate: 10-20g/min
 Packing details as follows

 - 10pcs/Carton Giftbox Size: 27.2x10.7x14.5cm

Carton Meas.: 57x28.5x31.5cm G.W./N.W.: 11/10Kgs. 20'=5590pcs; 40'=11830pcs; 40'HQ=13300pcs

Economic Steam Iron SG-5001

FUNCTIONS

- . Dry/spray/steam/burst of
- steam/self-cleaning
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control Optional features: anti-calc/
- anti-drip/auto shut-off Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 350ml
- Soleplate size: 229x121mm Unit size: 300x120x155mm
- Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- · Packing details as follows 10pcs/Carton Giftbox Size: 31.3x12.5x16.5cm

Carton Meas.: 65x32.5x35cm G.W./N.W.: 14/13Kgs. 20'=3950pcs; 40'=8100pcs; 40'HQ=9200pcs



FUNCTIONS

- · Dry/spray/steam/burst of steam/self-cleaning • Voltage:220-240V/10
 • Soleplate: Non-Stick/Ceramic • Frequency: 50/60Hz
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz

40'HQ=9200pcs

- · Water tank capacity: 340ml
- Soleplate size: 229x121mm Unit size: 300x120x155mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows 10pcs/Carton
- Giftbox Size: 31.3x12.5x16.5cm Carton Meas.: 65x32.5x35cm G.W./N.W.: 14/13Kgs. 20'=3950pcs: 40'=8100pcs:





Economic Steam Iron SG-5003

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning Voltage:220-240V/10
 Soleplate: Non-Stick/Ceramic Frequency: 50/60Hz coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz
- · Water tank capacity: 300ml
- Soleplate size: 229x121mm
 Unit size: 295x120x145mm
- . Burst of steam rate: 0.3-0.5g/time
- · Continuous steam rate: 15-25g/min
- · Packing details as follows 10pcs/Carton Giftbox Size: 31.8x12.6x14.7cm Carton Meas.: 65.5x33x31.5cm G.W./N.W.: 13/12Kgs.

20'=4100pcs; 40'=8600pcs;

Economic Steam Iron SG-5005

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning • Voltage:220-240V/10
 • Soleplate: Non-Stick/Ceramic • Frequency: 50/60Hz
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
 Optional features: anti-calc/
- anti-drip/auto shut-off
- Overheat safety protection circuit

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz
- Water tank capacity: 300ml
- Soleolate size: 229x121mm Unit size: 295x120x145.5mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- Packing details as follows 10pcs/Carton Giftbox Size: 31.3x12.5x16.5cm Carton Meas.: 65x32.5x35cm G.W./N.W.: 14/13Kgs.

20'=3950pcs; 40'=8100pcs;

40'HQ=9200pcs

CE/GS/CB/RoHS approval



Economic Steam Iron SG-5006

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- Optional features: anti-calc/ anti-drip/auto shut-off · Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

40'HQ=7960pcs

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
- Water tank capacity: 300ml
- Soleplate size: 229x121mm
- Unit size: 305x121x150mm · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min Packing details as follows

10pcs/Carton Giftbox Size: 32.8x13.3x16.2cm Carton Meas.: 55.4x33.9x34.4cm G.W./N.W.: 12/11Kgs. 20'=3064pcs; 40'=6520pcs;



Economic Steam Iron SG-5058

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- steel · High accurate temperature
- · Optional features: anti-calc/
- anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2200W
 Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz · Water tank capacity: 350ml
 - Soleplate size: 230x121mm
 Unit size: 295x120x150mm
 - . Burst of steam rate: 0.3-0.5g/time
 - Continuous steam rate: 15-25g/min
 - Packing details as follows

10pcs/Carton Giftbox Size: 30.5x12.4x15.7cm Carton Meas.: 65x31.5x33.5cm G.W./N.W.: 13/12Kgs. 20'=4150pcs; 40'=8310pcs; 40'HQ=9520pcs

Economic Steam Iron SG-5058G

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature · Optional features: anti-calc/
- anti-drip/auto shut-off Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz Water tank capacity: 350ml
- Soleplate size: 229x121mm
- Unit size: 295x120x150mm
- · Burst of steam rate: 0.3-0.5g/time Continuous steam rate: 15-25g/min
 Packing details as follows
- 10pcs/Carton Giftbox Size: 30.5x12.4x15.7cm Carton Meas.: 65x31.5x33.5cm G.W./N.W.: 13/12Kgs. 20'=4150pcs; 40'=8310pcs;

40'HQ=9520pcs





FUNCTIONS

- · Dry/spray/steam/burst of
- steam/self-cleaning
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc/ anti-drip/auto shut-off · Overheat safety protection
- CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 260ml
- Soleplate size: 229x121mm Unit size: 305x120x140mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min Packing details as follows
- 10pcs/Carton Giftbox Size: 32x12.5x15.3cm
- Carton Meas.: 65.5x33.3x33cm G.W./N.W.: 14.5/13.5Kgs. 20'=4060pcs; 40'=8120pcs; 40'HQ=9100pcs





Economic Steam Iron SG-5166

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off · Overheat safety protection

CE/GS/CB/ETL/CETL/RoHS

SPECIFICATIONS

- Power: 1200-2200W
 Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
 - · Water tank capacity: 300ml

 - Soleplate size: 230x120mm
 Unit size: 300x120x150mm
 - · Burst of steam rate: 0.3-0.5g/time
 - Continuous steam rate: 15-25g/min Packing details as follows 10pcs/Carton

Giftbox Size: 31.3x12.5x15.9cm Carton Meas.: 65.5x32.5x34cm G.W./N.W.: 14.5/13.5Kgs. 20'=3900pcs; 40'=8060pcs; 40'HQ=9500pcs

Economic Steam Iron SG-5028

FUNCTIONS

- . Dry/spray/steam/burst of steam/
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ auto shut-off
- Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2000W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz · Water tank capacity: 350ml
- Soleplate size: 229x120mm
- Unit size: 300x120x160mm
- · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min
 Packing details as follows 10pcs/Carton Carton Meas.: 65x32.5x35cm





Economic Steam Iron SG-5078

FUNCTIONS

- Dry/spray/steam/burst of
- steam/self-cleaning
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200-2200W
- Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
- Water tank capacity: 200ml
- Soleplate size: 229x120mm Unit size: 290x120x140mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min Packing details as follows
- 10pcs/Carton Giftbox Size: 29x12.2x14.4cm

Carton Meas.: 65x30x31.5cm G.W./N.W.: 12/11Kgs. 20'=4400pcs; 40'=9230pcs; 40'HQ=10900pcs



Economic Steam Iron SG-5288

FUNCTIONS

- Dry/spray/steam/burst of
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200W
- Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
- · Water tank capacity: 90ml
- Soleplate size: 200x109mm
 Unit size: 265x105x120mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min
- Packing details as follows 10pcs/Carton Giftbox Size: 27.2x11.2x13.8cm
- Carton Meas.: 59.5x28.5x30cm G.W./N.W.: 12/11Kgs. 20'=5280pcs; 40'=11190pcs; 40'HQ=12790pcs

Economic Steam Iron SG-5510A

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning
 Soleplate: Non-Stick/Ceramic
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature · Optional features: anti-calc/
- anti-drip/auto shut-off Overheat safety protection circuit
- CE/GS/CB/RoHS approval

SPECIFICATIONS

- Water tank capacity: 270ml
- Unit size: 293x133x145mm
- Continuous steam rate: 15-25g/min
- 10pcs/Carton
- G.W./N.W.: 13/12Kgs. 20'=4150pcs; 40'=8310pcs;

40'HQ=9520pcs



- Power: 1200-2600W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Soleplate size: 231x120mm
- · Burst of steam rate: 0.4-0.6g/time
- Packing details as follows
- Giftbox Size: 30.5x12.4x15.7cm Carton Meas.: 65x31.5x33.5cm

- Dry/spray/steam/burst of
- steam/ Voltage:220-240V/100-127V/50/60Hz
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Frequency: 50/60Hz
 Water tank capacity: 200ml Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc/
- auto shut-off · Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS

- Power: 1200W

- Soleplate size: 214x115mm
- Unit size: 280x115x140mm
 Burst of steam rate: 0.3-0.5g/time
- · Continuous steam rate: 15-25g/min
- Packing details as follows 10pcs/Carton

Giftbox Size: 28.7x11.8x15.7cm Carton Meas.: 62x30x33.5cm G.W./N.W.: 14.5/13.5Kgs, 20'=4380pcs; 40'=9280pcs; 40'HQ=10380pcs





Economic Steam Iron SG-5588

FUNCTIONS

- Dry/spray/steam/burst of
- steam/
 Soleplate: Non-Stick/Cerami coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Overheat safety protection circuit

CE/GS/CB/RoHS approval

- SPECIFICATIONS
- Power: 1200W
 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 120ml
 Soleplate size: 198x108mm
 Unit size: 255x110x125mm

- · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min Packing details as follows
- 10pcs/Carton Giftbox Size: 26.5x11.2x13cm Carton Meas.: 59.5x28x28.5cm G.W./N.W.: 12/11Kgs. 20'=5990pcs; 40'=12390pcs; 40'HQ=14400pcs

Economic Steam Iron SG-5888A

- FUNCTIONS SPECIFICATIONS

 Dry/spray/steam Power: 1200-1400W

 Soleplate: Non-Stick/Ceramic Voltage: 220-240V/100-127V/50/60Hz
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

- Frequency: 50/60Hz
- Water tank capacity: 60ml
 Soleplate size: 187x99mm
- Unit size: 230x100x105mm
- Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min
 Packing details as follows 10pcs/Carton

Giftbox Size: 23.8x10.3x11.8cm Carton Meas.: 54.5x25x25.5cm G.W./N.W.: 9/8Kgs. 20'=7900pcs; 40'=16180pcs; 40'HQ=17980pcs



Cord & rdbrod 6 se Stream femilieries

Cord & Cordless Steam Iron SG-5510

circuit

- FUNCTIONS

 Dry/spray/steam/burst of steam/self-cleaning
 Soleplate: Non-Stick/Ceramic
- coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS approval

- SPECIFICATIONS

 Power: 1200-2600W

 Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 270ml
- Soleplate size: 231x120mm
 Unit size: 320x133x145mm
- . Burst of steam rate: 0.4-0.6g/time
- Continuous steam rate: 15-25g/min
 Packing details as follows
- 10pcs/Carton Giftbox Size: 34.7x14.6x16.5cm

Carton Meas.: 46x35.7x35cm G.W./N.W.: 13/12Kgs. 20'=2958pcs; 40'=6000pcs; 40'HQ=6840pcs







Cord & Cordless Steam Iron SG-6001B

FUNCTIONS

- . Dry/spray/steam/burst of
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature control
- · Optional features: anti-calc
- CE/GS/CB/RoHS approval

Overheat safety protection

SPECIFICATIONS

- Power: 1200-1800W Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- · Water tank capacity: 200ml Soleplate size: 198x105mm
- Unit size: 282x107x220mm
- · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
- · Packing details as follows Giftbox Size: 29x12.5x21.5cm Carton Meas.: 65x30x45cm G.W./N.W.: 13.5/12.5Kgs. 20'=3230pcs; 40'=6560pcs;

40'HQ=7600pcs



Cordless Steam Iron SG-5588B

FUNCTIONS

- . Dry/spray/steam/burst of steam
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 120ml Soleplate size: 198x108mm
- Unit size: 270x107x220mm
- Burst of steam rate: 0.3-0.5g/time
 Continuous steam rate: 10-20g/min
 Packing details as follows
- 10pcs/Carton Giftbox Size: 27.5x12.6x20.6cm Carton Meas.: 66x28.5x43cm G.W./N.W.: 13/12Kgs. 20'=3600pcs; 40'=7260pcs;

40'HQ=8100pcs

Cord & Cordless Steam Iron SG-5068B

FUNCTIONS

- · Dry/spray/steam/burst of
- steam
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc
- · Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
 Water tank capacity: 180ml
- Soleplate size: 198x105mm
- Unit size: 280x107x210mm
- Burst of steam rate: 0.3-0.5g/time
 Continuous steam rate: 10-20g/min
- Packing details as follows 10pcs/Carton Giftbox Size: 26.5x12.2x21.5cm Carton Meas.: 63.5x27.6x45cm

G.W./N.W.: 13/12Kgs. 20'=3600pcs; 40'=7260pcs; 40'HQ=8100pcs





Cordless Steam Iron SG-5888B

FUNCTIONS

- Dry/spray/steam
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- steel · High accurate temperature
- · Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200W
- Voltage:220-240V/100-127V/50/60Hz • Frequency: 50/60Hz
 - Water tank capacity: 60ml
 Soleplate size: 187x99mm Unit size: 258x107x195mm
 - Burst of steam rate: 0.3-0.5g/time
 Continuous steam rate: 10-20g/min Packing details as follows
 - 10pcs/Carton Giftbox Size: 25.6x11.6x18.6cm Carton Meas::61x27x39cm

G.W./N.W.: 11/10Kgs. 20'=4550pcs; 40'=9100pcs; 40'HQ=9600pcs

Cordless Steam Iron SG-6001BN

FUNCTIONS

- Dry/spray/steam/burst of
- Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/ Titanium coating/stainless
- High accurate temperature control
- · Optional features: anti-calc Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
- Voltage:220-240V/100-127V/50/60Hz
- Frequency: 50/60Hz
- Water tank capacity: 200ml Soleplate size: 198x105mm
- Unit size: 265x117x220mm
- . Burst of steam rate: 0.3-0.5g/time Continuous steam rate: 15-25g/min
- · Packing details as follows

10pcs/Carton Giftbox Size: 29x12.5x21.5cm Carton Meas.: 65x30x45cm G.W./N.W.: 13.5/12.5Kgs. 20'=3230pcs; 40'=6560pcs; 40'HO=7600pcs



Cordless Steam Iron SG-5588BN

FUNCTIONS

- Dry/spray/steam/burst of steam
- · Overheat safety protection
- CE/GS/CB/RoHS approval

- Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/ Titanium coating/stainless
- · High accurate temperature

SPECIFICATIONS

40'HQ=8100pcs

- Power: 1200-1800W
- Voltage:220-240V/100-127V/50/60Hz Frequency: 50/60Hz
- Water tank capacity: 120ml Soleplate size: 198x108mm
- Unit size: 256x117x220mm
- Burst of steam rate: 0.3-0.5g/time
 Continuous steam rate: 10-20g/min
 Packing details as follows
- 10pcs/Carton Giftbox Size: 27.5x12.6x20.6cm Carton Meas.: 66x28.5x43cm G.W./N.W.: 13/12Kgs. 20'=3600pcs; 40'=7260pcs;

Cordless Steam Iron SG-5068BN

- **FUNCTIONS** · Dry/spray/steam/burst of
- steam Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/ Titanium coating/stainless
- High accurate temperature control
- · Optional features: anti-calc/ auto shut-off · Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-1800W
- Voltage:220-240V/100-127V/50/60Hz Frequency: 50/60Hz
 Water tank capacity: 180ml
- Soleplate size: 198x105mm Unit size: 280x107x210mm
 - Burst of steam rate: 0.3-0.5g/time Continuous steam rate: 10-20g/mir
 - Packing details as follows 10pcs/Carton Giftbox Size: 26.5x12.2x21.5cm Carton Meas.: 63.5x27.6x45cm

G.W./N.W.: 13/12Kgs. 20'=3600pcs; 40'=7260pcs; 40'HQ=8100pcs





Cordless Steam Iron SG-5888BN

FUNCTIONS

- Dry/spray/steam
 Soleplate: Non-Stick/Ceramic coating/Nano Ceramic/ Titanium coating/stainless steel
- · High accurate temperature
- Overheat safety protection

CE/GS/CB/RoHS approval

- **SPECIFICATIONS** Power: 1200W
- Voltage:220-240V/100-127V/50/60Hz Frequency: 50/60Hz
- Water tank capacity: 60ml
 Soleplate size: 187x99mm
- Unit size: 240x117x195mm
- Burst of steam rate: 0.3-0.5g/time
 Continuous steam rate: 10-20g/min
 Packing details as follows
- 10pcs/Carton

Giftbox Size: 25.6x11.6x18.6cm Carton Meas::61x27x39cm G.W./N.W.: 11/10Kgs.

20'=4550pcs; 40'=9100pcs; 40'HQ=9600pcs



Cord Retractable Steam Iron SG-5058C

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature
- · Optional features: anti-calc/
- anti-drip/auto shut-off · Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS

- Power: 1200W Voltage: 120V
- Water tank capacity: 350ml • Soleplate size: 229x121mm
- Unit size: 320x120x150mm
- . Burst of steam rate: 0.3-0.5g/time
- · Continuous steam rate: 15-25g/min Packing details as follows

10pcs/Carton Giftbox Size: 33.3x12.5x15.3cm Carton Meas.: 64.8x34.5x32.8cm G.W./N.W.: 16/15Kgs. 20'=3800pcs; 40'=7900pcs; 40'HQ=8840pcs





Cord Retractable Steam Iron SG-5002C

FUNCTIONS

circuit

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature control
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200WVoltage: 120V
- Water tank capacity: 340ml · Soleplate: Non-Stick/Ceramic Soleplate size: 229x121mm
 - Unit size: 330x120x155mm . Burst of steam rate: 0.3-0.5g/time
 - Continuous steam rate: 15-25g/min
 - · Packing details as follows 10pcs/Carton

Giftbox Size: 34.6x12.4x15.4cm Carton Meas.: 64.5x35.6x32.8cm G.W./N.W.: 16/15Kgs. 20'=3750pcs; 40'=7550pcs; 40'HQ=8390pcs

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature control
- · Optional features: anti-calc/ anti-drip/auto shut-off
- · Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL approval

SPECIFICATIONS


Power: 1200W

Cord Retractable Steam Iron SG-5078C

- · Voltage: 120V
- Water tank capacity: 200ml
- Soleplate size: 229x120mm Unit size: 315x120x140mm
- . Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min
 Packing details as follows
- 12pcs/Carton

40'HQ=12120pcs

Mail order box Size: 33x12.5x14cm Carton Meas.: 58x35.5x50.5cm G.W./N.W.: 13.5/12.5Kgs. 20'=3640pcs; 40'=6400pcs;





Cord Retractable Steam Iron SG-5098C

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200W Voltage: 120V
- Water tank capacity: 260ml

40'HQ=9350pcs

- Soleplate size: 229x121mm
- Unit size: 305x120x140mm
 - · Burst of steam rate: 0.3-0.5g/time Continuous steam rate: 15-25g/min
 - · Packing details as follows 10pcs/Carton Giftbox Size: 32x12.5x14.7cm Carton Meas.: 65.5x33.3x31.8cm G.W./N.W.: 14/13Kgs. 20'=4030pcs; 40'=8350pcs;





Cord Retractable Steam Iron SG-5166C

FUNCTIONS

circuit

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature control
- · Optional features: anti-calc/ anti-drip/auto shut-off Overheat safety protection
- CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200WVoltage: 120V
- Water tank capacity: 300ml Soleplate size: 230x120mm Unit size: 300x120x150mm
 - . Burst of steam rate: 0.3-0.5g/time
 - Continuous steam rate: 15-25g/min
 - Packing details as follows 10pcs/Carton Giftbox Size: 31.3x12.5x15.3cm

Carton Meas.: 65.5x32.5x33cm G.W./N.W.: 14/13Kgs. 20'=4100pcs; 40'=8300pcs; 40'HQ=9450pcs

Cord Retractable Steam Iron SG-5166C3

FUNCTIONS

- · Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless steel
- · High accurate temperature control Optional features: anti-calc/
- anti-drip/auto shut-off Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1200-2200W
- Voltage: 220-240V/100-127V
- Water tank capacity: 300ml
 Soleplate size: 230x120mm
- Unit size: 330x120x150mm · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 15-25g/min
 Packing details as follows

10pcs/Carton Giftbox Size: 34.2x12.5x15.5cm Carton Meas.:64.8x35.2x33.5cm G.W./N.W.: 16/15Kgs. 20'=3500pcs; 40'=7720pcs; 40'HQ=9160pcs



Cord Retractable Steam Iron SG-5001C

FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- · Optional features: anti-calc/ anti-drip/auto shut-off
- · Overheat safety protection circuit

CE/GS/CB/RoHS/ETL/CETL

SPECIFICATIONS

- Power: 1200W Voltage: 120V
- · Water tank capacity: 350ml
- Soleplate size: 229x121mm Unit size: 330x120x155mm
- . Burst of steam rate: 0.3-0.5g/time
- · Continuous steam rate: 15-25g/min
- · Packing details as follows 10pcs/Carton Giftbox Size: 34.6x12.4x15.4cm Carton Meas.:64.5x35.6x32.8cm
- G.W./N.W.: 16/15Kgs. 20'=3750pcs; 40'=7550pcs; 40'HQ=8390pcs





Cord Retractable Steam Iron SG-5288C


FUNCTIONS

- Dry/spray/steam/burst of steam/self-cleaning/Cord Retractable
- · Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control
- · Optional features: anti-calc/ anti-drip/auto shut-off
- Overheat safety protection

CE/GS/CB/RoHS/ETL/CETL

- SPECIFICATIONS Power: 1200W
- Voltage: 120V
- Water tank capacity: 90ml
 Soleplate size: 198x108mm
 Unit size: 290x105x120mm
- · Burst of steam rate: 0.3-0.5g/time
- Continuous steam rate: 10-20g/min
 Packing details as follows
- 6pcs/Carton

Giftbox Size: 30.5x11.2x12.8cm Carton Meas.:35.6x31.5x27.8cm G.W./N.W.: 13/12Kgs. 20'=5370pcs; 40'=11100pcs; 40'HQ=12480pcs



Dry Iron SG-5188A with Spray

FUNCTIONS

- Dry/spray
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- High accurate temperature control
- Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1000W
 Voltage:220-240V/100-127V/50/60Hz
 Water tank capacity: 30ml
 Soleplate size: 198x105mm
- Unit size: 260x105x120mm
- Packing details as follows 10pcs/Carton Giftbox Size: 26.5x10.9x13.1cm
- Carton Meas.:57.5x28x29cm G.W./N.W.: 10/9Kgs. 20'=6070pcs; 40'=12460pcs; 40'HQ=14020pcs



Dry Iron SG-5188B

FUNCTIONS

- Dry
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature
- Overheat safety protection circuit

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1000W
 Voltage:220-240V/100-127V/50/60Hz Soleplate size: 198x105mm
 - Unit size: 260x105x120mm

 - Packing details as follows 10pcs/Carton
 - Giftbox Size: 26.5x10.9x13.1cm
 - Carton Meas.:57.5x28x29cm G.W./N.W.: 10/9Kgs.
 - 20'=6070pcs; 40'=12460pcs; 40'HQ=14020pcs

Dry Iron SG-5188C

FUNCTIONS

- Dry
 Soleplate: Non-Stick/Ceramic coating/NanoCeramic/ Titanium coating/stainless
- · High accurate temperature control Overheat safety protection

CE/GS/CB/RoHS approval

SPECIFICATIONS

- Power: 1000W
- Voltage:220-240V/100-127V/50/60Hz
 Soleplate size: 198x105mm
- Unit size: 260x105x130mm Packing details as follows
- 10pcs/Carton Giftbox Size: 26.5x10.9x13.7cm

Carton Meas.:57.5x28x30cm G.W./N.W.: 10/9Kgs, 20'=6060pcs; 40'=12150pcs; 40'HQ=13670pcs













Soleplate Series

